

## BESTRUN S3

|                   |         |
|-------------------|---------|
| Product Reference | Bestrun |
| EN ISO 20345:2011 | S3 SRC  |
| Sizes             | 36-47   |
| Weight (s. 41)    | 590 gr. |

**Model description:** Leather shoe, water repellent, black, Nylon mesh lining, antistatic, puncture resistant steel sole, shock proof, antislip, steel toe cap, S3 PU/PU sole.

**Application areas:** Construction, Manufacturing.

**Precaution and maintenance of the shoe:** To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



|               |   | Description  | Measure Unit            | Result | EN345 required |
|---------------|---|--|-------------------------|--------|----------------|
| Complete shoe | Protection of toes: Metal tip resistant to:<br>A shock of 200 J<br>Pressure of 1500 kg<br>Sole: Metal Sole resistant to 1100N | Impact resistance (Clearance after shock)          | Mm                      | 15,5   | >14            |
|               |   | Compressive strength (after clearance compression) | Mm                      | 18,5   | 14             |
|               | Anti-shock system: Low-Density polyurethane and profile of the heel   | Shock absorption in heel                           | J                       | >35    | >20            |
| Upper         | Black leather, water repellent,   | Permeability to water vapor                        | Mg/m <sup>2</sup> hour  | >2,0   | >0,8           |
|               | Thickness 1,6mm   | Permeability coefficient                           | Mg/cm <sup>2</sup>      | >25,6  | >20            |
|               |   | Water repellent                                    | Minute                  | >90    | <60            |
| Front         | Thickness 1,2mm   | Permeability coefficient                           | Mg/cm <sup>2</sup>      | >35    | >30            |
| Lining        | Nylon mesh grey   | Permeability to water vapor                        | Mg/cm <sup>2</sup> hour | >2,1   | >2             |
| Back          | Thickness 1,0mm   | Permeability coefficient                           | Mg/cm <sup>2</sup>      | >45    | >30            |
| Insole        | Antistatic, absorbent, resistant to abrasion and to exfoliation   | Abrasion resistance                                | Cycles                  | >400   | >400           |
| Outsole       | Antistatic double density polyurethane injected directly onto the upper   | Abrasion resistance (volume loss)                  | Mm <sup>3</sup>         | 110    | <150           |
|               | Shock Absorption, anti-slip, abrasion resistant, mineral oils and weak acids  | Oil resistance (volume variation AV)               | %                       | +1,0   | <+12           |
|               |   | Coefficient of adhesion of the outsole             | -                       | 0,18   | >0,15          |

*Our shoes are constantly evolving, the technical data above may change.*

*All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.*