

EN 388:2016

CONSTRUCTO 3243X

Seamless cotton safety gloves for general use in heavy conditions

The seamless CONSTRUCTO gloves of Safety Jogger are designed for general use. Cotton/polyester liner with green latex coating on the palm of the hand. The most used glove for handling for which high abrasion resistance and dexterity are a must!

Extremely flexible and solid. The wrinkled latex coating gives an extraordinary grip.

Features

- Cotton/polyester glove
- Wrinkled latex grip

• 7, 8, 9, 10 and 11

- Extremely flexible and solid
- DMF free

Sizes

cotton/polyester glove

*TDM - 100 test

Performance level rating

EN388:2016	0	1	2	3		4	5
a. Abrasion resistance (cycles)	<100	100	500	200	0 8	000	-
b. Cut resistance (factor)	<1.2	1.2	2.5	5.0	1	0.0	20.0
c. Tear resistance (newton)	<10	10	25	50		75	-
d. Puncture resistance (newton)	<20	20	60	100 150		.50	-
EN ISO 13997 (TDM-100 test)		Α	В	С	D	E	F
e. Straight blade cut resistance (newton)			5	10	15	22	30

- a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
- b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
- c. Tear resistance: based on the amount of force required to tear the sample.
- d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
- e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.



WWW.SAFETYJOGGER.COM



SAFETY JOGGER GLOVES SIZE CHART



WORKS



- a. Hand length.
- b. Area where the hand circumference is measured.
- c. Binding color.

Glove size	a Hand length (mm)	b Hand circumference (mm)	c Binding color
7	17 1	178	🔴 Red
8	182	203	🥚 Yellow
9	192	229	Brown
10	204	254	Black
11	215	279	Blue