

**SAFETY DATA SHEET ACCORDING TO EC 1907/2006  
LYRECO SOLVENT BASED CORRECTION FLUID 139.418**

Revised on 12.06.2015 Page 1 to 4

**Section 1: Identification of the preparation and the company / undertaking**

1.1. Identification of the preparation

LYRECO Solvent Correction Fluid-20ml.

Purpose: Correction fluid for paper or fax copies.

1.2 Identification of the preparation and the company / undertaking

LYRECO

Rue du 19 mars 1962

59770 Marly

France

Tel: +33(0) 3 27 23 64 00

msds@lyreco.com

Emergency telephone number: Tel: +33(0) 3 27 23 64 00

**Section 2: Hazardous possibilities**

Harmful. Dangerous for the environment. Highly flammable. Injuries to health: can cause lung damage when swallowing. Irritating to respiratory system and skin. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

2.1. Risk phrases(R)

R 65-May cause lung damage if swallowed

R11-Highly flammable.

2.2. Safety phrases(S)

S23-Do not breathe vapour.

S24-Avoid contact with skin.

S25-Avoid contact with eyes.

S62-If swallowed, do not induce vomiting.

## Classification according to Regulation (EC) 1272/2008

Label elements:



Signal words

Irritant

Dangerous

Flammable

### Hazard Statement

H225-Highly flammable liquid and vapour

H319 -Causes serious eye irritation

H302 –Harmful if swallowed

H412-Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### Precautionary Statements

P305+P351+P338 if in eyes

Rinse cautiously with water for several minutes.

Remove contact lenses and continue rinsing.

P270-Do not eat, drink or smoke when using.

P273-Avoid emission in environment

P501-The content and packing to be thrown away according local laws.

### **Section 3: Composition / Information on ingredients.**

The correction fluid is a white coloured liquid, filled in plastic bottle composed with brush and plastic cap. The fluid contains organic solvent and non-hazardous additives and colouring agents. The main ingredients of the correction fluid are:

CAS	Ingredient	Conc. %	Symbols	R-Phrases	S-Phrases
93763-35-0	Solvent	>30	Xi Xn.F	11,65	23,24,25,62
13463-67-7	Titanium oxide	<20	none	none	22
471-34-1	Chalk	< 35	none	none	none

### **Section 4: First aid measures.**

In case of accident or if you feel unwell:

Seek medical advice immediately. If the patient is likely to become unconscious, place and transport in stable sideways position. In case of allergic symptoms, especially respiratory related, seek medical help immediately.

#### **First aid measures / Inhalation:**

Ensure supply of fresh air and seek medical advice.

**First aid measures / skin contact:**

Remove soiled or soaked clothing immediately. Do not allow drying. Clean body thoroughly (bath, shower). In case of contact with skin wash off immediately with soap and water /or Vaseline pharmaceutical grade/.

**First aid measures / eye contact:**

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice. (See 04).

**First aid measures / ingestion:**

Induce the patient to vomit of his/her own accord, only if fully conscious. When swallowed accidentally, do not induce vomiting, get medical help. When swallowed seek medical aid immediately and show the physician the packaging or the label of the packaging.

**Section 5: Fire fighting measures.**

Use suitable extinguisher. Foam, dry powder, carbon dioxide. Extinguishing media that must not be used for safety reasons is water or full water jet. Special exposure hazards arising from the substance or preparation itself, its combustion products or from resulting gases. Combustion gases of organic materials must in principle be graded as inhalation poisons. Special protective equipment for fire fighting must be used. Do not inhale combustion gases. In case of combustion use suitable breathing apparatus. Fire residues must be disposed of in a proper manner. Fire residues and contaminated fire fighting water must be disposed of in accordance with the local and national regulations.

**Section 6: Accidental release measures.****Personal precautions:**

Ensure adequate ventilation. Remove persons to safety. Keep people away and stay on the upwind side.

**Environmental precautions / Handling and storage: Chronic Cat. 3**

Do not allow to enter drains or waterways. Do not allow spilled product to enter soil or waterways.

**Section 7: Handling and Storage**

Take up with absorbent material (sand, kieselguhr, and sawdust). Pick up in containers capable of being locked. Clean contaminated floors and objects thoroughly with water and detergents, observing environmental regulations. Dispose of as prescribed. Clean equipment with solvents/gasoline, acetone.

**Section 8: Product in 20 ml. packs.**

There are not necessary special protective devices when product is used for correction of papersq, printed paper or fax copies.

**Section 9: Physical and chemical properties.**

**Appearance:** Liquid

**Colour:** White

**Odour:** Mild

**Density / method:** ca.1, 16 g/cm<sup>3</sup> DIN 53217 (23°C)

**Upper explosion limit:** 7.0% v.

**Solubility in water:** **insoluble.**

**Solvent content:** 40-45% m

#### **Section 10: Stability and reactivity.**

Mixtures of inflammable substances are easily combustible and burn vigorously even under exclusion of air. Unlearned empty vessels may contain product gases which can form explosive mixtures with air. No hazardous decomposition products known.

#### **Section 11: Toxicological information.**

No experimental information on genetic toxicity in vitro available. When inhaled in large quantities, the solvent vapours cause a narcotic effect. A sensitisation is possible for persons who are sensitive. Inhalation can cause damage to the respiratory system or lungs. No special hazards have to be mentioned.

#### **Section 12: Ecological information.**

Pigments are highly stable in accordance with the specifications and therefore only slightly biodegradable in the conditions of sewage treatment plants or surface waters/see point 6/

#### **Section 13: Disposal considerations.**

Waste code No.08 01 11 / Name of waste: Paints and lacquers wastes containing solvents.

#### **Section 14: Transport information.**

UN number: 1263 UN

Class : 3 II

LQ 6-when is in 20 ml. packs.

#### **Section 15: Regulatory information.**

.R-phrases: 11, 65.

S-phrases: 23,24,25,62.

Symbols: Xn,F,Xi

Highly flammable. Injuries to health: when swallowed lung damage can be caused. Irritating to respiratory system and eyes. Do not breathe vapour. Do not empty into drains.

#### **Section 16: Other information.**

The information contained in this safety data sheet is provided in accordance with the requirements of the Chemical (Hazard Information and Packaging) Regulations. The product should not be used for purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. The information contained in this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. Flammable. Highly flammable. Risk of serious damage to eyes. Injuries to health: when swallowed, can cause lung damage.